

< elseif >

Description

The < elseif > element is used within the conditional logic statement <if> and optional <else> element.

Syntax

```
<elseif  
cond="ECMAScript_Expression"/>
```

Attributes

cond	The cond attribute is the Boolean expression for the conditional logic statement. This attribute is required.
------	---

Parents

```
<if>
```

Children

None.

Extensions

None.

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
```

```
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <var name="card_type" expr="'amex'" />
  <form>
    <field name="card_num" type="digits">
      <prompt>What is your card number?</prompt>
      <filled>
        <if cond="card_type == 'amex' && card_num.length != 15">
          American Express card numbers must have 15 digits.
          <clear namelist="card_num"/>
        <elseif cond="card_type != 'amex' && card_num.length != 16"/>
          Mastercard and Visa card numbers have 16 digits.
          <clear namelist="card_num"/>
        </if>
      </filled>
    </field>
  </form>
</vxml>
```

From:
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:
https://wiki.voximal.com/doku.php?id=developer_guide:voicexml_references:elements:elseif

Last update: **2015/10/27 11:14**

