

< error >

Description

The < error > element catches an error event. This is a shorthand notation for <catch event="error"> that catches all events of type error.

Syntax

```
<error  
count="Integer"  
cond="ECMAScript_Expression">  
child elements  
</error>
```

Attributes

count	This attribute defines the event count, as in < catch > element. This attribute is optional.
cond	The cond attribute is a Boolean condition to test to see if the event is caught by the <error>. This attribute is optional.

Anonymous Variables

Two anonymous variables are available within the scope of the < catch > element: *_event – the event contains the name of the event that was thrown. *_message – the message contains the message string from the corresponding < throw > element, or a platform-defined value for events raised by the platform.

Parents

```
<field>, <form>, <initial>, <menu>, <object>, <record>, <subdialog>,  
<transfer>, <vxml>
```

Children

```
<assign>, <audio>, <clear>, <disconnect>, <enumerate>, <exit>, <goto>, <if>,  
<prompt>, <reprompt>, <return>, <script>, <submit>, <throw>, <value>, <var>
```

Extensions

None.

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
<vxmл version="2.0" xmlns="http://www.w3.org/2001/vxмl">
<error>
  <prompt>An error has occurred.</prompt>
  <exit/>
</error>
<form>
  <block>
    <audio expr="directory+'badaudio.wav' "/>
  </block>
</form>
</vxмl>
```

From:
<https://wiki.voximal.com/> - Voximal documentation



Permanent link:
https://wiki.voximal.com/doku.php?id=developer_guide:voicexml_references:elements:error

Last update: 2015/10/27 12:29