2025/06/05 00:56 1/2 < filled >

# < filled >

### **Description**

The < filled > element specifies an action to perform when some combinations of fields are filled by user input. It may occur as a child of the element, or as a child of a field item.

## **Syntax**

```
<filled
mode="all" | "any"
namelist="item1 item2 item3...">
child elements
</filled>
```

#### **Attributes**

mo	ode	This attribute cannot be defined when it is in a field item. There are 2 filled modes, all any. This attribute is optional and the default is all. all – the action is executed when all of the fields in namelist attribute are filled, and at least one has been filled by the last user input. any – the action is executed when any of the specified fields are filled by the last user input.
nar	melist	This attribute cannot be defined when it is in a field item. The namelist defines the fields to trigger. This attribute is optional and the default is list of all form's field items.

#### **Parents**

```
<field>, <form>, <object>, <record>, <subdialog>, <transfer>
```

### **Children**

## **Extensions**

None.

## Limitations/Restrictions

None.

### **Example Code**

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
<var name="card type" expr="'amex'" />
<form>
 <field name="card num" type="digits">
  prompt>What is your card number?
  <filled>
   <if cond="card_type == 'amex' & amp; & amp; card_num.length != 15">
    American Express card numbers must have 15 digits.
    <clear namelist="card num"/>
   <elseif cond="card_type != 'amex' &amp;&amp; card_num.length != 16"/>
    Mastercard and Visa card numbers have 16 digits.
    <clear namelist="card num"/>
   </if>
  </filled>
 </field>
</form>
</vxml>
```

From

https://wiki.voximal.com/ - Voximal documentation

Permanent link:

https://wiki.voximal.com/doku.php?id=developer\_guide:voicexml\_references:elements:filled

Last update: 2015/10/27 12:30



https://wiki.voximal.com/ Printed on 2025/06/05 00:56