

< noinput >

Description

The < noinput > element handles the event when the user does not give inputs in a field. This is a shorthand notation for < catch event="noinput" > that catches all events of type error.

Syntax

```
<noinput  
count="Integer"  
cond="ECMAScript_Expression">  
child elements  
</noinput>
```

Attributes

count	The count attribute indicates the event count as in the < catch > element. This attribute is optional.
cond	The cond attribute is a Boolean condition to test to see if the event is caught by the <noinput> element. This attribute is optional.

Parents

```
<field>, <form>, <initial>, <menu>, <object>, <record>, <subdialog>,  
<transfer>, <vxml>
```

Children

```
<assign>, <audio>, <clear>, <disconnect>, <enumerate>, <exit>, <goto>, <if>,  
<prompt>, <reprompt>, <return>, <script>, <submit>, <throw>, <value>, <var>
```

Extensions

None.

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
<vxm version="2.0" xmlns="http://www.w3.org/2001/vxml">
<form>
<field name="hello">
<grammar type="text/x-grammar-choice-dtmf">
  1 {hello}
</grammar>
<prompt>Say hello</prompt>
<noinput>Say something</noinput>
<filled>
  <prompt>Hello, world!</prompt>
</filled>
</field>
</form>
</vxm>
```

From:
<https://wiki.voximal.com/> - Voximal documentation

Permanent link:
https://wiki.voximal.com/doku.php?id=developer_guide:voicexml_references:elements:noinput

Last update: 2015/10/27 21:38

