

< return >

Description

The <return> element completes the execution of <subdialog> and returns control and data to a calling dialog.

Syntax

```
<return  
event="event"  
namelist="variable1 variable2 ..."/>
```

Attributes

event	Return and throw this event. Optional.
namelist	Space-separated list of variables to be returned to the calling dialog. Optional (Defaults to no variables)

Parents

```
<block>, <catch>, <error>, <filled>, <help>, <if>, <noinput>, <nomatch>
```

Children

None.

Extensions

None.

Limitations/Restrictions

None.

Example Code

The following shows the document that calls the subdialog:

```
<?xml version="1.0"?>
<vxm version="2.0" xmlns="http://www.w3.org/2001/vxml">
<form>
  <subdialog name="result" src="subdialog.vxml">
    <filled>
      <prompt>Your account number is <value expr="result.acctnum"/>
      Your phone number is <value expr="result.acctphone"/>
    </prompt>
    </filled>
  </subdialog>
</form>
</vxm>
```

The following shows the document containing the subdialog:

```
<?xml version="1.0"?>
<vxm version="2.0" xmlns="http://www.w3.org/2001/vxml">
<form id="basic">
  <field name="acctnum" type="digits">
    <prompt>
      What is your account number?
    </prompt>
  </field>
  <field name="acctphone" type="phone">
    <prompt>
      What is your home telephone number?
    </prompt>
    <filled>
      <return namelist="acctnum acctphone"/>
    </filled>
  </field>
</form>
</vxm>
```

From:
<https://wiki.voximal.com/> - Voximal documentation



Permanent link:
https://wiki.voximal.com/doku.php?id=developer_guide:voicexml_references:elements:return

Last update: 2015/10/27 21:43