

# Errors

Following is the list of errors that are generated by the VoiceXML Browser:

## **error.badfetch**

The interpreter context throws this event when a fetch of a resource has failed and the interpreter context has reached a place in the document interpretation where the fetch result is required.

## **error.badfetch**

In case of a fetch failure, the interpreter context returns the specific HTTP response code, `http.<response code>`.

## **error.semantic**

A run-time error was found in the VoiceXML document.

## **error.noauthorization**

The user is not authorized to perform the requested operation.

## **error.unsupported.format**

The requested resource has a format that is not supported by the platform, (not supported yet).

## **error.unsupported.language**

The platform does not support the language for either speech synthesis or speech recognition, (for TTS/ASR, not supported yet).

## **error.telephone.noauthorization**

The caller is not allowed to call the destination.

## **error.telephone.baddestination**

Destination URI is malformed.

## **error.telephone.noroute**

The platform is not able to place a call to the destination.

## **error.telephone.noresource**

The platform cannot allocate a resource to place the call.

## **error.grammar**

There is an error in the DTMF grammar.

## **error.application**

Thrown when there is a miscellaneous application error.

### **error.script**

There is an error with ECMAScript.

### **error.internal**

Internal interpreter server error.

From:  
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:  
[https://wiki.voximal.com/doku.php?id=developer\\_guide:voicexml\\_references:errors:start](https://wiki.voximal.com/doku.php?id=developer_guide:voicexml_references:errors:start)

Last update: **2015/10/13 21:17**

