

# < else >

## Description

The < else > element is used within the conditional logic statement <if> and optional <elseif> element.

## Syntax

```
<else/>
```

## Parents

```
<if>
```

## Children

None.

## Extensions

None.

## Limitations/Restrictions

None.

## Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <form>
    <field name="password">
      <prompt> what is the code word </prompt>
      <help> It is the name of a fruit </help>
      <noinput> I did not hear you. </noinput>
      <nomatch count="1"> Nope. Try again </nomatch>
```

```
<nomatch count="2"> Nope. Give it another try </nomatch>
<nomatch count="3">
  Sorry. You didn't get it three times. Bye
  <disconnect/>
</nomatch>
<filled>
  <if cond="password=='reset'">
    <clear namelist="password"/>
  <else/>
    This is correct.
  </if>
</filled>
</field>
</form>
</vxml>
```

From: <https://wiki.voximal.com/> - **Voximal documentation**

Permanent link: [https://wiki.voximal.com/doku.php?id=legacy:vxi\\_developer\\_guide:voicexml\\_references:elements:else](https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:elements:else)

Last update: **2017/07/28 23:53**

