

< enumerate >

Description

The < enumerate > element is an automatically generated description of the choices available for the user. It specifies a template that is applied to each choice in the order they appear in the < menu > element, or in the < field > element that contains < option > elements.

Syntax

```
<enumerate>  
child elements  
</enumerate>
```

Anonymous Variables

If <enumerate> is used with no content, it lists all choices. You can customize the content using the two anonymous variables that are available within the scope of the <enumerate> element: * _prompt - the prompt for the current choice. * _dtmf - the assigned DTMF sequence for the current choice.

Parents

```
<audio>, <catch>, <error>, <field>, <filled>, <help>, <if>, <menu>,  
<noinput>, <nomatch>, <prompt>
```

Children

```
<audio>, <value>, Speech Markup (SSML)
```

Extensions

None.

Limitations/Restrictions

The dtmf attributes in the <choice> tags must be specified.

Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <menu dtmf="true">
    <prompt>
      Welcome home.
    <enumerate>
      For <value expr="_prompt"/>, press <value expr="_dtmf"/>.
    </enumerate>
  </prompt>
  <choice dtmf="1" next="http://www.example.com/vxml/sports.vxml">
    sports
  </choice>
  <choice dtmf="2" next="http://www.example.com/weather.vxml">
    weather
  </choice>
  <choice dtmf="3" next="http://www.example.com/news.vxml">
    news
  </choice>
</menu>
</vxml>
```

From:
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:
https://wiki.voximal.com/doku.php?id=legacy:vx_i_developer_guide:voicexml_references:elements:enumerate

Last update: **2017/07/28 23:53**

