# < exit >

## Description

The < exit > element exits the interpreter session and returns control to the interpreter context, which determines what to do next. This element differs from the < return > element in that < exit > terminates all loaded elements while < return > returns from a < subdialog > invocation.

## Syntax

```
<exit
expr="ECMAScript_Expression"
namelist="item1 item2 item3..."/>
```

## Attributes

| | |
|---|---|
| expr | The expr attribute is the expression to be evaluated and returned. This attribute is optional and the value is sent to the call control. |
| namelist | The namelist attribute indicates variable names to be returned to interpreter context, and returns nothing by default. This attribute is optional. |

## Parents

```
<block>, <catch>, <error>, <filled>, <help>, <if>, <noinput>, <nomatch>
```

## Children

```
None.
```

## Extensions

```
None.
```

## Limitations/Restrictions

```
None.
```

# Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
 <error>
  <prompt>An error has occurred.</prompt>
  <exit expr="'ERROR'"/>
 </error>
 <form>
  <block>
   <audio expr="directory+'badaudio.wav'"/>
  </block>
 </form>
</vxml>
```

From:
https://wiki.voximal.com/ - **Voximal documentation**

Permanent link:
**https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:elements:exit**

Last update: **2017/07/28 23:53**