

< foreach >

Description

Iterates through an ECMAScript array of items. New in VoiceXML 2.1.

Syntax

```
<foreach  
array = "ECMAScript_Expression"  
item = "variable"  
>
```

Attributes

array	An ECMAScript expression that evaluates to an array. Required.
item	The variable that stores each array item upon each iteration of the loop. Required.

Parents

<block>, <catch>, <error>, <filled>, <foreach>, <help>, <if>, <noinput>, <nomatch>, <prompt>

Children

<assign>, <audio>, <break>, <clear>, <data>, <disconnect>, <enumerate>, <exit>, <foreach>, <goto>, <if>, <log>, <prompt>, <reprompt>, <return>, <script>, <submit>, <throw>, <value>, <var>

Extensions

None.

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
<vxml version="2.1"
  xmlns="http://www.w3.org/2001/vxml">
  <form id="play_fruit">
    <block>
      <!-- create an array of fruit names -->
      <var name="aFruit" expr="new Array('apples', 'oranges', 'pears',
'bananas')"/>

      Here's a list of fruit we have available today

      <!-- iterate throught through each item in the array -->
      <foreach item="fruit" array="aFruit">
        <value expr="fruit"/>
      </foreach>
    </block>
  </form>
</vxml>
```

From:
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:
https://wiki.voximal.com/doku.php?id=legacy:vx_i_developer_guide:voicexml_references:elements:foreach

Last update: **2017/07/28 23:53**

