

< submit >

Description

The <submit> element submits values to document server. It is similar to <goto> in that it results in a new document being obtained. Unlike <goto>, it lets you submit a list of variables to the document server via HTTP GET or HTTP POST.

Syntax

```
<submit
next="URI"
expr="ECMAScript_Expression"
namelist="variable1 variable2 ..."
method="get" | "post"
enctype="MIME_type"
fetchaudio="URI"
fetchhint="prefetch" | "safe"
fetchtimeout="time_interval"
maxage="time_interval"
maxstale="time_interval">
</submit>
```

Attributes

next	The next attribute is the URI to which the query is submitted. This attribute is required - specifically either next or expr is required.
expr	The expr attribute is an expression that yields the URI. This attribute is required - specifically either next or expr is required.
namelist	The namelist attribute is a space-separated list of variables to submit. This attribute is optional and defaults to nothing.
method	The method attribute specifies the query request method, get or post. This attribute is optional and defaults to get.
enctype	The enctype attribute is MIME encoding of the document. This attribute is optional and defaults to application/x-www-form-urlencoded. The following types are supported: * application/x-www-form-urlencoded. * multipart/form-data.
fetchaudio	The fetchaudio attribute is the URI of the audio to play while waiting for the next document to be fetched.
fetchhint	The fetchhint defines when the audio file should be retrieved. This attribute is optional. * prefetch - the audio file may be downloaded when the page is loaded. * safe - the audio file is loaded only when needed.
maxage	The maxage attribute indicates the maximum time in seconds that this document will use this file before fetching another copy. This attribute is optional.

maxstale	The maxstale attribute indicates the maximum time in seconds that this document will use a file that exceeded the maxage time. This attribute is optional.
----------	--

Parents

<block>, <catch>, <error>, <filled>, <help>, <if>, <noinput>, <nomatch>

Children

None.

Extensions

None.

Limitations/Restrictions

The attribute `fetchhint = prefetch` is not supported, and is optional in VoiceXML.

Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <form id="get_from_and_to_cities">
    <grammar src="from_to.grammar"/>
    <block>
      Welcome to the Driving Directions By Phone.
    </block>
    <initial name="bypass_init">
      <prompt>Where do you want to drive from and to?</prompt>
      <nomatch count="1">
        Please say something like this,
        "from Toronto Ontario to Ottawa Ontario".
      </nomatch>
      <nomatch count="2">
        I'm sorry, I still don't understand.
        I'll ask you for information one piece at a time.
        <assign name="bypass_init" expr="true"/>
        <reprompt/>
      </nomatch>
    </initial>
  </form>
</vxml>
```

```
</initial>
<field name="from_city">
  <grammar src="city.grammar"/>
  <prompt>From which city are you leaving?</prompt>
  ...
</field>
<field name="to_city">
  <grammar src="city.grammar"/>
  <prompt>Which city are you going to?</prompt>
  ...
</field>
<block>
  <prompt>Retrieving directions</prompt>
  <submit next="direction.cgi" method="post"
  namelist="from_city to_city"/>
</block>
</form>
</vxml>
```

From:
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:
https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:elements:submit

Last update: **2017/07/28 23:53**

