

# < value >

## Description

The <value> element inserts the value of an expression in a prompt.

## Syntax

```
<value  
  expr="ECMAScript_Expression"/>
```

## Attributes

expr	The expr attribute is an expression to return. This attribute is required.
------	--

## Parents

```
<audio>, <block>, <catch>, <choice>, <enumerate>, <error>, <field>,  
<filled>, <help>, <if>, <initial>, <menu>, <noinput>, <nomatch>, <object>,  
<prompt>, <record>, <subdialog>, <transfer>
```

## Children

None.

## Extensions

None.

## Limitations/Restrictions

None.

## Example Code

```
<?xml version="1.0"?>
```

```
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <form>
    <field name="maincourse">
      <noinput> <reprompt/> </noinput>
      <nomatch> <reprompt/> </nomatch>
      <prompt count="1">Please select an entree.</prompt>
      <prompt count="2">Today, we're featuring:<enumerate/></prompt>
      <option dtmf="1" value="fish">swordfish</option>
      <option dtmf="2" value="beef">roast beef</option>
      <option dtmf="3" value="frog">frog legs</option>
      <filled>
        <prompt>
          <value expr="maincourse"/>, good choice.
          Please enjoy your meal.
        </prompt>
        <submit next="maincourse.cgi" method="post"
namelist="maincourse"/>
      </filled>
    </field>
  </form>
</vxml>
```

From: <https://wiki.voximal.com/> - **Voximal documentation**

Permanent link: [https://wiki.voximal.com/doku.php?id=legacy:vx\\_i\\_developer\\_guide:voicexml\\_references:elements:value](https://wiki.voximal.com/doku.php?id=legacy:vx_i_developer_guide:voicexml_references:elements:value)

Last update: **2017/07/28 23:53**

