

Errors

Following is the list of errors that are generated by the VoiceXML Browser:

error.badfetch

The interpreter context throws this event when a fetch of a resource has failed and the interpreter context has reached a place in the document interpretation where the fetch result is required.

error.badfetch

In case of a fetch failure, the interpreter context returns the specific HTTP response code, `http.<response code>`.

error.semantic

A run-time error was found in the VoiceXML document.

error.noauthorization

The user is not authorized to perform the requested operation.

error.unsupported.format

The requested resource has a format that is not supported by the platform, (not supported yet).

error.unsupported.language

The platform does not support the language for either speech synthesis or speech recognition, (for TTS/ASR, not supported yet).

error.telephone.noauthorization

The caller is not allowed to call the destination.

error.telephone.baddestination

Destination URI is malformed.

error.telephone.noroute

The platform is not able to place a call to the destination.

error.telephone.noresource

The platform cannot allocate a resource to place the call.

error.grammar

There is an error in the DTMF grammar.

error.application

Thrown when there is a miscellaneous application error.

error.script

There is an error with ECMAScript.

error.internal

Internal interpreter server error.

From:
<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:
https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:errors:start

Last update: **2017/07/28 23:53**

