

< initial >

Description

The < initial > element declares initial logic upon entry into a mixed-initiative form. Unlike < field >, < initial > has no grammars and no < filled > action. < initial > can request user input and handle events. < initial > continues to be visited while its form item variable is undefined and its condition is true. When any of the form's fields are filled in by user input, then all < initial > form item variables are set to true, before any < filled > actions are executed. Then the form will visit those fields that are still unfilled to complete the form.

Syntax

```
<initial
name="String"
expr="ECMAScript_Expression"
cond="ECMAScript_Expression">
child elements
</initial>
```

Attributes

name	The name attribute represents the name of form item variable used. Use this variable if you want to explicitly control the <initial> execution. This attribute is optional and defaults to an inaccessible internal variable.
expr	The expr attribute is the initial value of the form item variable. < initial > will be visited only if the expression evaluates to undefined. This attribute is optional and defaults to undefined.
cond	The cond attribute is a Boolean condition that must evaluate to true in order for the <initial> element to be visited. This attribute is optional and defaults to true.

Parents

```
<form>
```

Children

```
<audio>, <catch>, <error>, <help>, <link>, <noinput>, <nomatch>, <prompt>,
<property>, <value>
```

Extensions

None.

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <form id="product">
    <grammar type="text/x-grammar-choice-dtmf">
      1 {uno} |
      2 {dos} |
      3 {tres} |
      4 {cuatro} |
      5 {cinco}
    </grammar>
    <block>
      Welcome to the Product Information By Phone.
    </block>
    <initial name="id_product">
      <prompt>Enter the product ID?</prompt>
      <nomatch count="1">
        Please say something like this,
        "1 2 2 3 4".
      </nomatch>
      <nomatch count="2">
        I'm sorry, I still don't understand.
        I'll ask you for information one piece at a time.
        <assign name="id_product" expr="true"/>
        <reprompt/>
      </nomatch>
    </initial>
    <field name="color_product">
      <prompt>From which city are you leaving?</prompt>
    </field>
    <field name="form_product">
      <prompt>Which city are you going to?</prompt>
    </field>
    <block>
      <prompt>
        You said that you wanted <value expr="color_product"/>
      </prompt>
    </block>
  </form>
</vxml>
```

```
<value expr="color_product"/>.  
</prompt>  
</block>  
</form>  
</vxml>
```

From:

<https://wiki.voximal.com/> - **Voximal documentation**

Permanent link:

https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:elements:initial

Last update: **2017/07/28 23:53**

