

< log >

Description

The < log > element allows the application to generate debug messages. This element can contain a combination of text and <value> elements in which the resulting message will be the concatenation of the text and string value of the < value > element. The messages will be logged to the metrics file for viewing.

Syntax

```
<log  
expr="ECMAScript_Expression"  
label="String">  
text  
</log>
```

Attributes

expr	The expr attribute is a string expression that will be appended to the < log > element content and label. This attribute is optional.
label	The label attribute is a string label that will be appended to the < log > element content before expr. This attribute is optional.

Parents

```
<block>, <catch>, <error>, <filled>, <help>, <if>, <noinput>, <nomatch>
```

Children

```
<value>
```

Extensions

```
None.
```

Limitations/Restrictions

None.

Example Code

```
<?xml version="1.0"?>
<vxm version="2.0" xmlns="http://www.w3.org/2001/vxml">
<form>
  <field name="hello">
    <grammar type="text/x-grammar-choice-dtmf">
      1 {hello} | 2 {world}
    </grammar>
    <prompt>Say hello</prompt>
    <noinput>Say something</noinput>
    <filled>
      <log>The user said <value expr="hello"/>.</log>
      <prompt>Hello, world!</prompt>
    </filled>
  </field>
</form>
</vxm>
```

From:
<https://wiki.voximal.com/> - Voximal documentation

Permanent link:
https://wiki.voximal.com/doku.php?id=legacy:vxi_developer_guide:voicexml_references:elements:log

Last update: 2017/07/28 23:53

