

# < nomatch >

## Description

The < nomatch > element handles the event when the user gives unrecognized input. This is a shorthand notation for <catch event="nomatch"> that catches all events of type error.

## Syntax

```
<nomatch
count="Integer"
cond="ECMAScript_Expression">
  child elements
</nomatch>
```

## Attributes

|       |                                                                                                                                         |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------|
| count | The count attribute is the event count as in the < catch > element. This attribute is optional.                                         |
| cond  | The cond attribute is a Boolean condition to test to see if the event is caught by the < noinput > element. This attribute is optional. |

## Parents

```
<field>, <form>, <initial>, <menu>, <object>, <record>, <subdialog>,
<transfer>, <vxml>
```

## Children

```
<assign>, <audio>, <clear>, <disconnect>, <enumerate>, <exit>, <goto>, <if>,
<prompt>, <reprompt>, <return>, <script>, <submit>, <throw>, <value>, <var>
```

## Extensions

None .

## Limitations/Restrictions

None .

## Example Code

```
<?xml version="1.0"?>
<vxml version="2.0" xmlns="http://www.w3.org/2001/vxml">
  <form>
    <field name="hello">
      <grammar type="text/x-grammar-choice-dtmf">
        1 {hello}
      </grammar>
      <prompt>Say hello</prompt>
      <nomatch>That's not hello</nomatch>
      <filled>
        <prompt>Hello, world!</prompt>
      </filled>
    </field>
  </form>
</vxml>
```

From:  
<https://wiki.voximal.com/> - Voximal documentation

Permanent link:  
[https://wiki.voximal.com/doku.php?id=legacy:vxj\\_developer\\_guide:voicexml\\_references:elements:nomatch](https://wiki.voximal.com/doku.php?id=legacy:vxj_developer_guide:voicexml_references:elements:nomatch)

Last update: **2017/07/28 23:53**

